

SOUND POWERED TELEPHONE SYSTEMS

TELEPHONES

TYPE: SCM-TA

MODEL: TA-CJ-4CI

(Telephone + watertight box)

SCM
SISTEMAS



FEATURES

- Excellent speech quality.
- 12 extensions selector switch (extending up to 24).
- Acoustic and luminous alarms incorporated.
- Suitable for high-noise level areas.
- Waterproof housing.
- Material: GW plastic 120° (RAL 7035).
- Earpiece: ABS plastic (fireproof).
Spiral cord (60 cm extensible to 1.5 m).
- Available headphone connection for noisy areas:
Model: TA-ACM-A.

TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +50°C
Acoustic alarm	104 dB(A) (1m)
Luminous alarm	21W - 90 flash/min
Alarms supply	24 VDC - 25W
Relative humidity	Up to 95% (non condensing)
Assembly	Bulkhead
Weight	Approx 5.5 kg
IP-rating	55
Resistive load	10A 250VAC / 30VDC
Inductive load	($\cos\phi = 0.4$; L/R = 7 ms) 5A250VAC / 30VDC

SOUND POWERED TELEPHONE SYSTEMS

TELEPHONES

TYPE: SCM-TA

MODEL: TA-CJ-4CI

(Telephone + watertight box)

SCM
SISTEMAS

