

SOUND POWERED TELEPHONE SYSTEMS

TELEPHONES

TYPE: SCM-TA-MG

MODEL: TA-MG-3-P
(Portable telephone)

SCM
SISTEMAS



FEATURES

- Portable sound-powered telephone.
- Excellent speech quality.
- 12 extensions selector switch (extending up to 24).
- For use on open air deck areas and bridge wings.
- Material: ABS polymer (fireproof).
- Earpiece: ABS polymer (fireproof).
Spiral cord (60 cm extensible to 1.5 m)
- Available headphone connection for noisy areas:
Model: TA-ACM-A.
- Optional acoustic/luminous alarm via relay box.
- Includes metallic cableglands.

TECHNICAL SPECIFICATIONS

Operating temperature	-20°C to +70°C
Acoustic alarm	104 dB (1m)
Relative humidity	Up to 95% (non condensing)
Assembly	Portable
Weight	Approx 3 kg.
IP-rating	55
Resistive load	10A 250VAC / 30VDC
Inductive load	($\cos\phi = 0.4$; L/R = 7 ms) 5A250VAC / 30VDC

SOUND POWERED TELEPHONE SYSTEMS

TELEPHONES

TYPE: SCM-TA-MG

MODEL: TA-MG-3-P
(Portable telephone)

SCM
SISTEMAS

